SAFETY DATA SHEET

Revision Number 1

Revision Date 01-Apr-2015 Issuing Date No data available

The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is @ 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE **COMPANY/UNDERTAKING**

Product identifier

Product Name WM64684 Super Tech Fuel Injector Cleaner 6 FL.OZ.

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Fuel additive

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Technical Chemical Co.

Supplier Address 3327 Pipeline Road

> Box 139 Cleburne TX 76033 US

Supplier Phone Number Phone:800-424-9300

Fax:817-645-6088

Contact Phone817-645-6088

mhutchinson@technicalchemical.com **Supplier Email**

Emergency telephone number

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

•	,
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 4



GHS Label elements, including precautionary statements

Emergency Overview

Signal word

Danger

Hazard Statements

May cause genetic defects Suspected of causing cancer May be fatal if swallowed and enters airways Combustible liquid



Appearance Clear to light yellow

Physical State Liquid

Odor Mild

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

0.9% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Toxic to aquatic life with long lasting effects

PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION



Page 2/11

INHALATION MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS

Interactions with Other Chemicals

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
Petroleum distillates, hydrotreated light	64742-47-8	60 - 100	*
Naphtha (petroleum), hydrotreated heavy	64742-48-9	0.1 - 1	*
Ethylbenzene	100-41-4	0.1 - 1	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice Immediate medical attention is required. Show this safety data sheet to the doctor

in attendance.

Eye Contact Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist,

call a physician.

Skin Contact Wash with soap and water.

Inhalation Aspiration into lungs can produce severe lung damage. If breathing has stopped,

give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Seek immediate

medical attention/advice. Delayed pulmonary edema may occur.

Ingestion Aspiration hazard if swallowed - can enter lungs and cause damage. Do NOT

induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control

center immediately.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take

precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Wear personal protective clothing (see

section 8). Remove all sources of ignition.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Difficulty in breathing. Coughing and/ or wheezing. Dizziness. **Effects**

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.



Page 3/11

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray.

Uniform Fire Code Combustible Liquid: III-A

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid contact with eyes. Ensure adequate ventilation. Use personal protective equipment

as required. Evacuate personnel to safe areas. See section 8 for more information. Take precautionary measures against static discharges. Do not touch or walk through spilled

material.

Other Information Refer to protective measures listed in Sections 7 and 8.

Environmental Precautions

Environmental Precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage

if safe to do so.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so. Do not touch or walk through spilled

material. Dike far ahead of liquid spill for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling



Do not breathe dust/fume/gas/mist/vapors/spray.

Conditions for safe storage, including any incompatibilities

Storage Store locked up. Keep containers tightly closed in a dry, cool and well-ventilated place.

> Protect from moisture. Keep out of the reach of children. Store away from other materials. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Store in accordance with

the particular national regulations. Store in accordance with local regulations.

Incompatible Products None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Handling

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Petroleum distillates, hydrotreated light 64742-47-8	TWA: 5 mg/m³ STEL: 10 mg/m³ (as oil mist)	TWA: 5 mg/m³ (as oil mist)	
Ethylbenzene 100- 41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m³ STEL: 125 ppm STEL: 545 mg/m³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992)

Appropriate engineering controls

Engineering Measures Showers

> Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Tight sealing safety goggles.

Skin and Body Protection Wear protective gloves and protective clothing.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or

smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the

workplace.

Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES



Page 5/11

Physical and Chemical Properties

Physical State Liquid

Appearance Clear to light yellow Odor Mild

Color No information available Odor Threshold No information available

Property Values Remarks Method

pН 8 None known Melting / freezing point None known No data available Boiling point / boiling range No data available None known **Flash Point** 86 C / 187 F None known **Evaporation Rate** No data available None known Flammability (solid, gas) No data available None known

Flammability Limit in Air

Upper flammability limit No data available Lower flammability limit No data available

No data available None known Vapor pressure No data available None known Vapor density No data available None known **Specific Gravity** Insoluble in water **Water Solubility** None known Solubility in other solvents No data available None known Partition coefficient: n-octanol/waterNo data available None known **Autoignition temperature** No data available None known **Decomposition temperature** No data available None known Kinematic viscosity No data available None known Dynamic viscosity No data available None known

Explosive properties

Oxidizing Properties

No data available
No data available

Other Information

Softening Point

VOC Content (%)

Particle Size

No data available

No data available

No data available

Particle Size Distribution

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions None

under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

None known based on information supplied.

Hazardous Decomposition Products

Carbon oxides.



Page 6/11

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. Aspiration into lungs can

produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be

fatal. May cause irritation of respiratory tract.

Eye Contact Specific test data for the substance or mixture is not available. May cause irritation.

Skin Contact Repeated exposure may cause skin dryness or cracking.

Ingestion Specific test data for the substance or mixture is not available. Potential for aspiration if

swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary

edema and pneumonitis. May be fatal if swallowed and enters airways.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	> 5.2 mg/L (Rat)4 h
Naphtha (petroleum), hydrotreated heavy 64742-48-9	> 5000 mg/kg (Rat)	> 3160 mg/kg(Rabbit)	-
Ethylbenzene 100- 41-4	= 3500 mg/kg (Rat)	= 15354 mg/kg (Rabbit)	= 17.2 mg/L (Rat)4 h

Information on toxicological effects

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Asthma-like and/ or skin allergy-like

symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects Contains a known or suspected mutagen.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethylbenzene 100-	A3	Group 2B		X
41-4				

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive No information **Toxicity** available.

STOT - single No information

exposure available.

STOT - repeated No information

exposure available.

Chronic Toxicity Contains a known or suspected

mutagen. Possible risk of irreversible effects. Contains a known or suspected



Page 7/11

carcinogen. Aspiration may cause

pulmonary edema and pneumonitis.

Target Organ Effects May affect the genetic material in germ cells (sperm and eggs). Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Liver. Kidney. Thyroid. Central Vascular System (CVS). Testes.

Aspiration Hazard

No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document Not applicable

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Petroleum distillates, hydrotreated light 64742-47-8		96h LC50: = 2.2 mg/L (Lepomis macrochirus) 96h LC50: = 2.4 mg/L (Oncorhynchus mykiss) 96h LC50: = 45 mg/L (Pimephales promelas)		96h LC50: = 4720 mg/L
Naphtha (petroleum), hydrotreated heavy 64742-48-9		96h LC50: = 2200 mg/L (Pimephales promelas)		96h LC50: = 2.6 mg/L
Ethylbenzene 100- 41-4	72h EC50: = 4.6 mg/L (Pseudokirchneriella subcapitata) 96h EC50: > 438 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 2.6 - 11.3 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 1.7 - 7.6 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 11.0 - 18.0 mg/L (Oncorhynchus mykiss) 96h LC50: = 4.2 mg/L (Oncorhynchus mykiss) 96h LC50: 7.55 - 11 mg/L (Pimephales promelas) 96h LC50: = 32 mg/L (Lepomis macrochirus) 96h LC50: 9.1 - 15.6 mg/L (Pimephales promelas) 96h LC50: = 9.6 mg/L (Poecilia reticulata)		48h EC50: 1.8 - 2.4 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

Chemical Name	Log Pow
Ethylbenzene 100-	3.118
41-4	

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS



Page 8/11

Waste treatment methods

Disposal methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Dispose of contents/containers in accordance with local regulations.

С	hemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
	Ethylbenzene 100- 41-4		Included in waste stream: F039		

California Hazardous Waste Codes 213

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Ethylbenzene	Toxic
100-41-4	Ignitable

14. TRANSPORT INFORMATION

DOT NOT REGULATED

Proper Shipping Name NON REGULATED

Hazard Class N/A

TDG Not regulated

MEX Not regulated

ICAO Not regulated

Not regulated

<u>IATA</u>

Proper Shipping Name NON REGULATED

Hazard Class N/A

Not regulated

IMDG/IMO

Hazard Class N/A

RID Not regulated

ADR Not regulated

ADN Not regulated



Page 9/11

15. REGULATORY INFORMATION

International Inventories

TSCA Complies

DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Ethylbenzene - 100-41-4	100-41-4	0.1 - 1	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard Yes Chronic Health Hazard Yes

Fire Hazard Yes

Sudden release of pressure hazard No

Reactive Hazard No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ethylbenzene 100- 41-4	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Ethylbenzene 100- 41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Ethylbenzene - 100-41-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name Rhode Island **New Jersey** Massachusetts Pennsylvania Illinois Xylene, mixed isomers 1330-Х Х Χ Χ 20-7 Ethylbenzene 100-Χ Х Χ Χ Х 41-4



International Regulations

Component	Carcinogen Status	Exposure Limits
Ethylbenzene		Mexico: TWA 100 ppm
100-41-4 (0.1 - 1)		Mexico: TWA 435 mg/m ³
		Mexico: STEL 125 ppm
		Mexico: STEL 545 mg/m ³

Canada

WHMIS Hazard Class

B3 - Combustible liquid D2A - Very toxic materials D2B - Toxic materials



16. OTHER INFORMATION

NFPA Health Hazards 2 Flammability 2 Instability 0 Physical and

Chemical Hazards -

HMIS Health Hazards 2* Flammability 2 Physical Hazard 0 Personal Protection

Χ

Chronic Hazard Star Legend * = Chronic Health Hazard

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

Revision Date 01-Apr-2015

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

